

Lining  
04.84104883-0001

**Fixture details**

|                 |                 |
|-----------------|-----------------|
| Mounting        | Pendant         |
| Light emission  | Direct-Indirect |
| Fitting cover   | satin diffusor  |
| Protection rate | IP 20           |
| Housing         | Aluminium       |
| Finish          | anodized finish |
| Certificates    | CE, ISO 9001    |



**Electric details**

|                  |                        |
|------------------|------------------------|
| Protection class | I                      |
| Supply           | 230V                   |
| Control gear box | Current driver DALI/TD |

**Lamp details**

|                     |                            |
|---------------------|----------------------------|
| Lamptype            | LED 3000K                  |
| Wattage             | 6,7W                       |
| Gross luminous flux | 20320                      |
| Luminaire power     | 122,3W                     |
| Number              | 8                          |
| Lifetime LED module | L80/B10 > 72000h           |
| Color tolerance     | MacAdam 3                  |
| CRI                 | >80<br>+ 8x LED 3000K 7,2W |

**Photometric details**

|                       |                |
|-----------------------|----------------|
| UGR                   | >19            |
| CIE Fluxcode          | 49 80 96 99 65 |
| CIE Fluxcode Indirect | 00 00 00 00 73 |

**Dimensions**

|   |         |
|---|---------|
| A | 2322 mm |
| B | 60 mm   |
| C | 200 mm  |

**Remarks**

Suspended luminaire - Direct - HO 225mA - satin (flush) - ANO



**ENERGY**

Verkrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**WXYZ**  
kWh/1000h

**MULTILINE®**

2019/2015