

Nhua - satin - HO 325mA - ANO
05.19004683-0001

Fixture details

| | |
|-----------------|-----------------|
| Mounting | Ceiling |
| Light emission | Direct-Indirect |
| Fitting cover | satin diffusor |
| Protection rate | IP 40 |
| Housing | Aluminium |
| Finish | anodized finish |
| Certificates | CE, ISO 9001 |



Electric details

| | |
|------------------|------------------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Current driver DALI/TD |

Lamp details

| | |
|---------------------|------------------|
| Lamptype | LED 3000K |
| Wattage | 7,2W |
| Gross luminous flux | 10240 |
| Luminaire power | 63,4W |
| Number | 8 |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 |

Photometric details

| | |
|--------------|----------------|
| UGR | >19 |
| CIE Fluxcode | 34 61 83 76 75 |

Dimensions

| | |
|---|---------|
| A | 2254 mm |
|---|---------|

Remarks

Ceiling luminaire - HO 325mA - satin - ANO



ENERGY

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

WXYZ
kWh/1000h

MULTILINE®

2019/2015