

Rekta 30 SAPP - satin - HO 325mA - emergency - RAL  
07.23005604-9999

**Fixture details**

Mounting	Ceiling recessed
Light emission	Direct
Fitting cover	satin diffusor
Protection rate	IP 20
Housing	Aluminium
Finish	RAL colour at your choice
Certificates	CE, ISO 9001



**Electric details**

Protection class	I
Supply	230V
Control gear box	Current driver DALI/TD
Emergency set	Autonomy 1 hour DALI

**Lamp details**

Lamptype	LED 4000K
Wattage	7,2W
Gross luminous flux	13400
Luminaire power	79,2W
Number	10
Lifetime LED module	L80/B10 > 72000h
Color tolerance	MacAdam 3
CRI	>80

**Photometric details**

UGR	28,0/28,3
CIE Fluxcode	50 80 96 100 67

**Dimensions**

A	2804 mm
---	---------

**Remarks**

satin LED diffusor 325mA emergency module autonomy 1 hour



**ENERGY**

A  
 Verkrijgbaar op aanvraag.  
B  
 Disponible sur demande.  
C  
D  
 Available on request.  
E  
F  
 Auf Anfrage.  
G

**WXYZ**  
kWh/1000h

**MULTILINE®** 2019/2015