

Score curved Direct - satin - HO 325mA - RAL  
04.87204654-9999

**Fixture details**

|                 |                           |
|-----------------|---------------------------|
| Mounting        | Pendant                   |
| Light emission  | Direct                    |
| Fitting cover   | satin diffusor            |
| Protection rate | IP 20                     |
| Housing         | Aluminium                 |
| Finish          | RAL colour at your choice |
| Certificates    | CE, ISO 9001              |

**Electric details**

|                  |                        |
|------------------|------------------------|
| Protection class | I                      |
| Supply           | 230V                   |
| Control gear box | Current driver DALI/TD |

**Lamp details**

|                     |                  |
|---------------------|------------------|
| Lamptype            | LED 4000K        |
| Wattage             | 7,2W             |
| Gross luminous flux | 6700             |
| Luminaire power     | 39,6W            |
| Number              | 5                |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance     | MacAdam 3        |
| CRI                 | >80              |

**Photometric details**

|              |                |
|--------------|----------------|
| UGR          | >19            |
| CIE Fluxcode | 54 85 98 99 72 |

**Dimensions**

|   |         |
|---|---------|
| A | 1424 mm |
|---|---------|

**Remarks**

Suspended luminaire - Direct - HO 325mA - satin - RAL



**ENERGY**

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**WXYZ**  
kWh/1000h

**MULTILINE®**

2019/2015