

Tube 90 - Naked module - HO 150mA - transit wired
35.39115544-0000

Fixture details

| | |
|-----------------|------------------|
| Mounting | Ceiling recessed |
| Light emission | Direct |
| Fitting cover | satin diffusor |
| Protection rate | IP 65 |
| Housing | Polycarbonate |
| Finish | frosted |
| Certificates | CE, ISO 9001 |

Electric details

| | |
|------------------|------------------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Current driver DALI/TD |
| Emergency set | Autonomy 1 hour DALI |

Lamp details

| | |
|---------------------|------------------|
| Lamptype | LED 4000K |
| Wattage | 3,2W |
| Gross luminous flux | 2680 |
| Luminaire power | 14,1W |
| Number | 4 |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 |

Photometric details

| | |
|--------------|-----------------|
| CIE Fluxcode | 48 78 94 100 61 |
|--------------|-----------------|

Dimensions

| | |
|---|---------|
| A | 1130 mm |
|---|---------|

Remarks

Ceiling recessed luminaire - Naked module - HO 150mA - transit wiring



ENERGY

Verkrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

MULTILINE®

WXYZ
kWh/1000h

2019/2015