

Sferio Direct - satin - MO - RAL 9006  
04.36004144-9006

**Fixture details**

|                 |                          |
|-----------------|--------------------------|
| Mounting        | Pendant                  |
| Light emission  | Direct                   |
| Fitting cover   | Opal diffuser            |
| Protection rate | IP 20                    |
| Housing         | Aluminium                |
| Finish          | RAL 9006 White aluminium |
| Certificates    | CE, ISO 9001             |



**Electric details**

|                  |                   |
|------------------|-------------------|
| Protection class | I                 |
| Supply           | 230V              |
| Control gear box | Power supply DALI |

**Lamp details**

|                         |                  |
|-------------------------|------------------|
| Lamptype                | LED 4000K        |
| Wattage                 | 52W              |
| Luminaire power         | 52W              |
| Luminaire luminous flux | 7470             |
| Number                  | 1                |
| Lifetime LED module     | L80/B10 = 50000h |
| Color tolerance         | MacAdam 3        |
| CRI                     | >80              |

**Photometric details**

|              |                  |
|--------------|------------------|
| UGR          | >19              |
| CIE Fluxcode | 47 78 95 100 100 |

**Dimensions**

|   |        |
|---|--------|
| A | 600 mm |
|---|--------|

**Remarks**

Suspended luminaire - Direct - satin - MO - RAL 9006



**ENERGY**

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**WXYZ**  
kWh/1000h

**MULTILINE®**

2019/2015