

Sferio Direct - MPO - LO - RAL 9003  
07.36014044-9003

**Fixture details**

|                 |                          |
|-----------------|--------------------------|
| Mounting        | Ceiling recessed         |
| Light emission  | Direct                   |
| Fitting cover   | micro prismatic diffuser |
| Protection rate | IP 20                    |
| Housing         | Aluminium                |
| Finish          | RAL 9003 Signal white    |
| Certificates    | CE, ISO 9001             |



**Electric details**

|                  |                   |
|------------------|-------------------|
| Protection class | I                 |
| Supply           | 230V              |
| Control gear box | Power supply DALI |

**Lamp details**

|                         |                  |
|-------------------------|------------------|
| Lamptype                | LED 4000K        |
| Wattage                 | 28W              |
| Luminaire power         | 28W              |
| Luminaire luminous flux | 3860             |
| Number                  | 1                |
| Lifetime LED module     | L80/B10 = 50000h |
| Color tolerance         | MacAdam 3        |
| CRI                     | >80              |

**Photometric details**

|              |                  |
|--------------|------------------|
| UGR          | <19              |
| CIE Fluxcode | 60 87 97 100 100 |

**Dimensions**

|   |        |
|---|--------|
| A | 650 mm |
|---|--------|

**Remarks**

Recessed luminaire (trimless) - Direct - MPO - LO - RAL 9003



**ENERGY**

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**WXYZ**  
kWh/1000h

**MULTILINE®**

2019/2015