

Hideline 65x90 Direct/Indirect - VDT - LO 400mA - RAL  
04.70320184-9999

**Fixture details**

|                 |                           |
|-----------------|---------------------------|
| Mounting        | Pendant                   |
| Light emission  | Direct-Indirect           |
| Fitting cover   | VDT louvre                |
| Protection rate | IP 20                     |
| Housing         | Aluminium                 |
| Finish          | RAL colour at your choice |
| Certificates    | CE, ISO 9001              |

**Electric details**

|                  |                |
|------------------|----------------|
| Protection class | I              |
| Supply           | 230V           |
| Control gear box | Current driver |

**Lamp details**

|                     |                  |
|---------------------|------------------|
| Lamptype            | LED 4000K        |
| Wattage             | 4,5W             |
| Gross luminous flux | 12300            |
| Luminaire power     | 74,3W            |
| Number              | 15               |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance     | MacAdam 3        |
| CRI                 | >80              |

**Photometric details**

|                       |                  |
|-----------------------|------------------|
| UGR                   | <19              |
| CIE Fluxcode          | 90 99 100 100 68 |
| CIE Fluxcode Indirect | 00 00 00 00 67   |

**Dimensions**

|   |         |
|---|---------|
| A | 2250 mm |
|---|---------|

**Remarks**

Suspended luminaire - Direct/Indirect - LO 400mA - VDT louvre - RAL



**ENERGY**

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**MULTILINE®** WXYZ kWh/1000h

2019/2015