

Rekta 80x100 Direct - satin - HO 325mA - ANO  
07.68000604-0001

**Fixture details**

|                 |                  |
|-----------------|------------------|
| Mounting        | Ceiling recessed |
| Light emission  | Direct           |
| Fitting cover   | satin diffusor   |
| Protection rate | IP 20            |
| Housing         | Aluminium        |
| Finish          | anodized finish  |
| Certificates    | CE, ISO 9001     |

**Electric details**

|                  |                |
|------------------|----------------|
| Protection class | I              |
| Supply           | 230V           |
| Control gear box | Current driver |

**Lamp details**

|                     |                  |
|---------------------|------------------|
| Lamptype            | LED 4000K        |
| Wattage             | 7,2W             |
| Gross luminous flux | 13400            |
| Luminaire power     | 79,2W            |
| Number              | 10               |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance     | MacAdam 3        |
| CRI                 | >80              |

**Photometric details**

|              |                 |
|--------------|-----------------|
| UGR          | >19             |
| CIE Fluxcode | 54 83 97 100 69 |

**Dimensions**

|   |         |
|---|---------|
| A | 2804 mm |
|---|---------|

**Remarks**

Recessed luminaire (trimless) - Direct - HO 325mA - satin - ANO



**ENERGY**  


Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**WXYZ**  
kWh/1000h

**MULTILINE®** 

2019/2015