

Sferio Direct - satin - LO - RAL 9003  
05.36004033-9003

**Fixture details**

|                 |                       |
|-----------------|-----------------------|
| Mounting        | Ceiling               |
| Light emission  | Direct                |
| Fitting cover   | Opal diffuser         |
| Protection rate | IP 20                 |
| Housing         | Aluminium             |
| Finish          | RAL 9003 Signal white |
| Certificates    | CE, ISO 9001          |

**Electric details**

|                  |                   |
|------------------|-------------------|
| Protection class | I                 |
| Supply           | 230V              |
| Control gear box | Power supply DALI |

**Lamp details**

|                         |                  |
|-------------------------|------------------|
| Lamptype                | LED 3000K        |
| Wattage                 | 18W              |
| Luminaire power         | 18W              |
| Luminaire luminous flux | 2384             |
| Number                  | 1                |
| Lifetime LED module     | L80/B10 = 50000h |
| Color tolerance         | MacAdam 3        |
| CRI                     | >80              |

**Photometric details**


|              |                  |
|--------------|------------------|
| UGR          | >19              |
| CIE Fluxcode | 47 78 95 100 100 |

**Dimensions**

|   |        |
|---|--------|
| A | 500 mm |
|---|--------|

**Remarks**

Ceiling luminaire - Direct - satin - LO - RAL 9003



**ENERGY**

Verkrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**WXYZ**  
kWh/1000h

**MULTILINE®**

2019/2015