

Sferio Direct - satin - LO - RAL 9003  
05.36006034-9003

**Fixture details**

|                 |                       |
|-----------------|-----------------------|
| Mounting        | Ceiling               |
| Light emission  | Direct                |
| Fitting cover   | Opal diffuser         |
| Protection rate | IP 20                 |
| Housing         | Aluminium             |
| Finish          | RAL 9003 Signal white |
| Certificates    | CE, ISO 9001          |

**Electric details**

|                  |                        |
|------------------|------------------------|
| Protection class | I                      |
| Supply           | 230V                   |
| Control gear box | Power supply touch-dim |

**Lamp details**

|                         |                  |
|-------------------------|------------------|
| Lamptype                | LED 4000K        |
| Wattage                 | 18W              |
| Luminaire power         | 18W              |
| Luminaire luminous flux | 2550             |
| Number                  | 1                |
| Lifetime LED module     | L80/B10 = 50000h |
| Color tolerance         | MacAdam 3        |
| CRI                     | >80              |

**Photometric details**

|              |                  |
|--------------|------------------|
| UGR          | >19              |
| CIE Fluxcode | 47 78 95 100 100 |

**Dimensions**

|   |        |
|---|--------|
| A | 500 mm |
|---|--------|

**Remarks**

Ceiling luminaire - Direct - satin - LO - RAL 9003



**ENERGY**

A  
 Verkrijgbaar op aanvraag.  
B  
 Disponible sur demande.  
C  
D  
 Available on request.  
E  
F  
 Auf Anfrage.  
G

**WXYZ**  
kWh/1000h

**MULTILINE®** 2019/2015