

Sferio Direct/Indirect - MPO - MO - RAL 9006  
05.36112153-9006

**Fixture details**

|                 |                          |
|-----------------|--------------------------|
| Mounting        | Ceiling                  |
| Light emission  | Direct-Indirect          |
| Fitting cover   | micro prismatic diffuser |
| Protection rate | IP 20                    |
| Housing         | Aluminium                |
| Finish          | RAL 9006 White aluminium |
| Certificates    | CE, ISO 9001             |



**Electric details**

|                  |                      |
|------------------|----------------------|
| Protection class | I                    |
| Supply           | 230V                 |
| Control gear box | Current driver 1-10V |

**Lamp details**

|                         |                  |
|-------------------------|------------------|
| Lamptype                | LED 3000K        |
| Wattage                 | 144W             |
| Luminaire power         | 144W             |
| Luminaire luminous flux | 16185            |
| Number                  | 1                |
| Lifetime LED module     | L80/B10 = 50000h |
| Color tolerance         | MacAdam 3        |
| CRI                     | >80              |

**Photometric details**



|              |                 |
|--------------|-----------------|
| UGR          | <19             |
| CIE Fluxcode | 60 87 97 56 100 |

**Dimensions**

|   |        |
|---|--------|
| A | 900 mm |
|---|--------|

**Remarks**

Ceiling luminaire - Direct/Indirect - MPO - MO - RAL 9006



**ENERGY**

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**WXYZ**  
kWh/1000h

**MULTILINE®**

2019/2015