

Anilo Direct - satin - MO - RAL 9005  
05.49000104-9005

**Fixture details**

|                 |                    |
|-----------------|--------------------|
| Mounting        | Ceiling            |
| Light emission  | Direct             |
| Fitting cover   | Opal diffuser      |
| Protection rate | IP 20              |
| Housing         | Aluminium          |
| Finish          | RAL 9005 Jet black |
| Certificates    | CE, ISO 9001       |



**Electric details**

|                  |                |
|------------------|----------------|
| Protection class | I              |
| Supply           | 230V           |
| Control gear box | Current driver |

**Lamp details**

|                         |                  |
|-------------------------|------------------|
| Lamptype                | LED 4000K        |
| Wattage                 | 25W              |
| Luminaire power         | 25W              |
| Luminaire luminous flux | 2060             |
| Number                  | 1                |
| Lifetime LED module     | L80/B10 = 50000h |
| Color tolerance         | MacAdam 3        |
| CRI                     | >80              |

**Photometric details**

|              |                  |
|--------------|------------------|
| UGR          | >19              |
| CIE Fluxcode | 47 78 95 100 100 |

**Dimensions**

|   |        |
|---|--------|
| A | 600 mm |
|---|--------|

**Remarks**

Ceiling luminaire - Direct - satin - MO - RAL 9005



**ENERGY**

Verkrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**WXYZ**  
kWh/1000h

**MULTILINE®**

2019/2015